

Technical Documentation

# **XH0756C**

## **Optim TEXP | AEHHXF**

Date: May 28, 2018

### Technical Data Sheet

Motor Type: AEHHXF

Catalogue No: XH0756C

#### Nameplate Information

HP	Pole	RPM	Frame	Voltage	Hz	Phase
75	6	1180	405TC	230 / 460	60	3
Enclosure	Ins. Class	Service Factor	Time Rating	NEMA Design	Rated Amb.	Rated Altitude
TEXP	F	1.15	Continuous	B	-40 to 40°C °C	<3300 ft

#### Typical Performance

Efficiency (%)				Power Factor (%)		
Full Load		3/4 Load	1/2 Load	Full Load	3/4 Load	1/2 Load
Nom.	Min.					
94.5	93.6	95.0	95.0	86.5	85.0	79.0
Torque				Current (A)		
Full Load (lb-ft)	Locked Rotor (% FLT)	Pull Up (% FLT)	Break Down (% FLT)	No Load	Full Load	Locked Rotor
334	185	155	220	46.4 / 23.2	172.0 / 85.9	1085 / 543
NEMA KVA Code	Inertia (WR <sup>2</sup> )			Safe Stall Time (s)		Noise Level Sound Press. dB(A)
	Rotor (lb-ft <sup>2</sup> )	NEMA Load (lb-ft <sup>2</sup> )	Max. Allowable (lb-ft <sup>2</sup> )	Cold	Hot	
G	32.453	904	1543	17	12	70

#### VFD Duty Information

Speed Range			VFD		S.F.
Constant Torque	Variable Torque	Constant Power	Carrier	Type	
6-60Hz	3-60Hz	60-90Hz	≤ 5 kHz	VPWM or CPWM	1.0 Only

#### Additional Information

Bearings		Approx. Weight
DE	NDE	lbs
6317	6313	1408

#### Hazardous Locations Information

CSA/UL Certified	
Class I, Div 1, Groups D; Class II, Div 1, Groups E, F & G Class I, Zone 1, Groups IIA; Class II, Div 1, Groups E, F & G	
Temp Code (Sinewave / VFD)	T3B / T3B

**Nameplate Drawing**

# Optim TEXP

TYPE	AEHHXF	CAT. NO.	XH0756C		
OUTPUT	75 HP 56 kW	FRAME	405TC	TEXP	
R.P.M.	1180	POLE	6	INS.	F
VOLTS	230 / 460	PHASE	3	Hz	60
AMPS	172.0 / 85.9	CODE	G	S.F.	1.15
AMBIENT	40 °C	NOM. EFF. 94.5		MIN. EFF. 93.6	
BEARINGS	6317 / 6313			RATING Cont.	
SER. NO.	TBD	DESIGN	B	WT. 1408 LBS	
PWM VFD DUTY	VT	CT	CP	S.F.	
	3-60Hz	6-60Hz	60-90Hz	1.0 Only	

**Connection Diagram**




12 LEAD DUAL VOLTAGE WYE/DELTA						
VOLTAGE	CONNECTION		L1	L2	L3	JOIN
HIGH	START	WYE	1	2	3	4&7,5&8,6&9 10&11&12
	RUN	DELTA	1,12	2,10	3,11	4&7,5&8,6&9
LOW	START	2 WYE	1,7	2,8	3,9	4&5&6 10&11&12
	RUN	2 DELTA	1,6,7 12	2,4,8 10	3,5,9 11	

WD\_12YD

**Thermal Limit Curves**

Motor Type: AEHHXF		Catalogue No: XH0756C		Family: Optim TEXP	
HP	75	Safe Stall Time		Full Load A	172.0 / 85.9 A
Voltage	230 / 460V 60Hz	Hot	12 s	Locked Rotor A	631 / 632 %
RPM	1200	Cold	17 s	Locked Rotor A	1,085.0 / 543 A



**T-N and I-N Curves**

Motor Type: AEHHXF		Catalogue No: XH0756C		Family: Optim TEXP	
HP	75	Full Load T	334 lb-ft	Full Load A	172.0 / 85.9 A
Voltage	230 / 460V 60Hz	Locked Rotor T	185 %	Locked Rotor A	1,085.0 / 543.0 A
RPM	1200	Pull Up T	155 %	Break Down T	220 %

