

Technical Documentation


CJM05045

Optim JM | AEHH8N_JM

Date: November 29, 2016

Dimensional Drawing

Catalogue	Model	HP	Pole	kW	Rating	Voltage	Hz	RPM
CJM05045	AEHH8N_JM	50	4	37	Continuous	575 V	60	1800



AEHH8N-JM-SMP-7

Frame Size		Mounting					A	B	C	CD	D
		E	2F	2F2	H	BA					
326JM		6.25	12		0.66	5.5	15.75	12.8	31.67		8
G	J	K	L	M	O	P	T	Key			Keyseat
								Width	Thick	Length	R
1.11	3.15				16.22	16.54	2.36	0.25	0.25	2.52	1.112
Terminal Housing				Aux Box		C/D Flange					
AA	AB	AC	XB	AE	AX	BB	AH	AK	BD	AJ	BF
2"	14.65	11.3	3.59			0.25	5.25	12.5	13.59	11	4-5/8"-11UNC
Shaft Extension			Bearings		Approx. Weight Lbs	SPL dBA/3ft	Ins. Class	S.F.	Drive Method	Dimensions	
N-W	U	V	DE	NDE							
	1.25		6312	6212	719	76	F	1.15	DirectCoupling	Inches	

Technical Data Sheet

Motor Type: AEHH8N_JM

Catalogue No: CJM05045

Nameplate Information

HP	Pole	RPM	Frame	Voltage	Hz	Phase
50	4	1770	326JM	575	60	3
Enclosure	Ins. Class	Service Factor	Time Rating	NEMA Design	Rated Amb.	Rated Altitude
TEFC	F	1.15	Continuous	B	-40 to 40 °C	<3300 ft

Typical Performance

Efficiency (%)				Power Factor (%)		
Full Load		3/4 Load	1/2 Load	Full Load	3/4 Load	1/2 Load
Nom.	Min.					
94.5	93.6	95.0	95.0	87.0	86.0	80.5
Torque				Current (A)		
Full Load (lb-ft)	Locked Rotor (% FLT)	Pull Up (% FLT)	Break Down (% FLT)	No Load	Full Load	Locked Rotor
148.30	210	170	220	10.5	45.6	290
NEMA KVA Code	Inertia (WR ²)			Safe Stall Time (s)		Noise Level Sound Press. dB(A)
	Rotor (lb-ft ²)	NEMA Load (lb-ft ²)	Max. Allowable (lb-ft ²)	Cold	Hot	
G	10.123	232	427	17	12	76

VFD Duty Information

Speed Range			VFD		S.F.
Constant Torque	Variable Torque	Constant Power	Carrier	Type	
6-60Hz	3-60Hz	60-90Hz	≤ 5 kHz	VPWM or CPWM	1.0 Only


Additional Information

Bearings		Approx. Weight
DE	NDE	lbs
6312	6212	719

Hazardous Locations Information

CSA Certified	
Class I, Div 2, Groups B, C & D Class I, Zone 2, Groups IIB+H2, IIB & IIA	
Temp Code (Sinewave / VFD)	T3C / T3

Connection Diagram




3 LEAD SINGLE VOLTAGE DELTA					
VOLTAGE	CONN.	L1	L2	L3	
-	DELTA	1	2	3	

WD_3D

Thermal Limit Curves

Motor Type: AEHH8N_JM		Catalogue No: CJM05045		Family: Optim JM	
HP	50	Safe Stall Time		Full Load A	0.0 / 45.6 A
Voltage	0 / 575V 60Hz	Hot	12 s	Locked Rotor A	637 %
RPM	1800	Cold	17 s	Locked Rotor A	0.0 / 290 A



T-N and I-N Curves

Motor Type: AEHH8N_JM		Catalogue No: CJM05045		Family: Optim JM	
HP	50	Full Load T	148.30 lb-ft	Full Load A	45.6 A
Voltage	575V 60Hz	Locked Rotor T	210 %	Locked Rotor A	290.0 A
RPM	1800	Pull Up T	170 %	Break Down T	220 %

