

Technical Documentation


# **PDX05025**

## **Optim TEFC | AEHH8N**

Date: July 1, 2021

**Dimensional Drawing**

Catalogue	Type	HP	RPM	Voltage	Hz	Frame Size
PDX05025	AEHH8N	50	3600	575	60	326TS(X)



Mounting					A	B	C	CL1	CL2	D	G
E	2F1	2F2	H	BA							
6.25	12	10.5	0.67	5.25	15.75	16.34	31.45			8	1.1

J	K	L	M	O	P	T
3.15		15.47	11.95	15.5	15.91	2.36

Terminal Housing			
AA	AB	AC	XB
2	16.07	12.2	3.59

Shaft Extension			Key			Keyseat
N-W	U	V	Width	Thick	Length	R
3.75	1.875	3.65	0.5	0.5	2.03	1.591

Bearings		Weight Lbs	Drive Method	Dimensions
DE	NDE			
6312C3	6310C3	638	Direct Coupling	Inches

### Technical Data Sheet

Motor Type: AEHH8N

Catalogue No: PDX05025

#### Nameplate Information

HP	Pole	RPM	Frame	Voltage	Hz	Phase
50	2	3550	326TS(X)	575	60	3
Enclosure	Ins. Class	Service Factor	Time Rating	NEMA Design	Rated Amb.	Rated Altitude
TEFC	F	1.15	Continuous	B	-40 to 40 °C	<1000 m

#### Typical Performance

Efficiency (%)				Power Factor (%)		
Full Load		3/4 Load	1/2 Load	Full Load	3/4 Load	1/2 Load
Nom.	Min.					
93.00	91.70	93.70	93.00	92.00	91.00	89.00
Torque				Current (A)		
Full Load (lb-ft)	Locked Rotor (% FLT)	Pull Up (% FLT)	Break Down (% FLT)	No Load	Full Load	Locked Rotor
74.15	230	200	250	6.6	43.8	290.40
NEMA KVA Code	Inertia (WR <sup>2</sup> )			Safe Stall Time (s)		Noise Level Sound Press. dB(A)
	Rotor (lb-ft <sup>2</sup> )	NEMA Load (lb-ft <sup>2</sup> )	Max. Allowable (lb-ft <sup>2</sup> )	Cold	Hot	
G	3.229	49.00	147.00	17	12	78.0

#### VFD Duty Information

Speed Range			VFD		S.F.
Constant Torque	Variable Torque	Constant Power	Carrier	Type	
6-60Hz	3-60Hz	60-75Hz	0	VPWM or CPWM	1.0 Only

#### Hazardous Locations Information

CSA Certified	
Class I, Div 2, Groups B, C & D Class I, Zone 2, Groups IIB+H2, IIB & IIA	
Temp Code (Sinewave / VFD)	T3 / T3

#### Additional Certifications

Other Certification
---------------------

#### Additional Information

Bearings		Approx. Weight
DE	NDE	lbs
6312C3	6310C3	638

**Nameplate Drawing**

# Optim TEFC

TYPE	AEHH8N	CAT. NO.	PDX05025		
OUTPUT	50 HP 37.30 kW	FRAME	326TS(X)	TEFC	
R.P.M.	3550	POLE	2	INS.	F
VOLTS	575	PHASE	3	Hz	60
AMPS	43.8	CODE	G	S.F.	1.15
AMBIENT	40 °C	NOM. EFF. 93.00		MIN. EFF. 91.70	
BEARINGS	6312C3 / 6310C3			RATING Cont.	
SER. NO.	TBD	DESIGN	B	WT. 638 LBS	
PWM VFD DUTY	VT	CT	CP	S.F.	
	3-60Hz	6-60Hz	60-75Hz	1.0 Only	

**Connection Diagram**




3 LEAD		SINGLE VOLTAGE			DELTA
VOLTAGE	CONN.	L1	L2	L3	
-	DELTA	1	2	3	

WD\_3D

### Thermal Limit Curves

Motor Type: AEHH8N		Catalogue No: PDX05025		Family: Optim TEFC	
HP	50	Safe Stall Time		Full Load A	43.8 A
Voltage	575V 60Hz	Hot	12 s	% Inrush	663 %
RPM	3600	Cold	17 s	Locked Rotor A	290.40 A



**T-N and I-N Curves**

Motor Type: AEHH8N		Catalogue No: PDX05025		Family: Optim TEFC	
HP	50	Full Load T	74.15 lb-ft	Full Load A	43.8 A
Voltage	575V 60Hz	Locked Rotor T	230 %	Locked Rotor A	290.4 A
RPM	3600	Pull Up T	200 %	Break Down T	250 %

