

Technical Documentation

XH0502C

Optim TEXP | AEHHXF

Date: May 28, 2018

Technical Data Sheet

Motor Type: AEHHXF

Catalogue No: XH0502C

Nameplate Information

HP	Pole	RPM	Frame	Voltage	Hz	Phase
50	2	3550	326TSC	230 / 460	60	3
Enclosure	Ins. Class	Service Factor	Time Rating	NEMA Design	Rated Amb.	Rated Altitude
TEXP	F	1.15	Continuous	B	-40 to 40°C °C	<3300 ft

Typical Performance

Efficiency (%)				Power Factor (%)		
Full Load		3/4 Load	1/2 Load	Full Load	3/4 Load	1/2 Load
Nom.	Min.					
93.6	92.4	94.0	94.0	91.0	91.0	89.0
Torque				Current (A)		
Full Load (lb-ft)	Locked Rotor (% FLT)	Pull Up (% FLT)	Break Down (% FLT)	No Load	Full Load	Locked Rotor
74	185	115	240	16.4 / 8.2	110.0 / 55.0	725 / 363
NEMA KVA Code	Inertia (WR ²)			Safe Stall Time (s)		Noise Level Sound Press. dB(A)
	Rotor (lb-ft ²)	NEMA Load (lb-ft ²)	Max. Allowable (lb-ft ²)	Cold	Hot	
G	4.488	49	88	17	12	78

VFD Duty Information

Speed Range			VFD		S.F.
Constant Torque	Variable Torque	Constant Power	Carrier	Type	
6-60Hz	3-60Hz	60-90Hz	≤ 5 kHz	VPWM or CPWM	1.0 Only

Additional Information

Bearings		Approx. Weight
DE	NDE	lbs
6312C3	6212C3	766

Hazardous Locations Information

CSA/UL Certified	
Class I, Div 1, Groups D; Class II, Div 1, Groups E, F & G Class I, Zone 1, Groups IIA; Class II, Div 1, Groups E, F & G	
Temp Code (Sinewave / VFD)	T3B / T3B

Nameplate Drawing

Optim TEXP

TYPE	AEHHXF	CAT. NO.	XH0502C		
OUTPUT	50 HP 37 kW	FRAME	326TSC	TEXP	
R.P.M.	3550	POLE	2	INS.	F
VOLTS	230 / 460	PHASE	3	Hz	60
AMPS	110.0 / 55.0	CODE	G	S.F.	1.15
AMBIENT	40 °C	NOM. EFF. 93.6		MIN. EFF. 92.4	
BEARINGS	6312C3 / 6212C3			RATING Cont.	
SER. NO.	TBD	DESIGN	B	WT. 766 LBS	
PWM VFD DUTY	VT	CT	CP	S.F.	
	3-60Hz	6-60Hz	60-90Hz	1.0 Only	

Connection Diagram




12 LEAD DUAL VOLTAGE WYE/DELTA						
VOLTAGE	CONNECTION		L1	L2	L3	JOIN
HIGH	START	WYE	1	2	3	4&7,5&8,6&9 10&11&12
	RUN	DELTA	1,12	2,10	3,11	4&7,5&8,6&9
LOW	START	2 WYE	1,7	2,8	3,9	4&5&6 10&11&12
	RUN	2 DELTA	1,6,7 12	2,4,8 10	3,5,9 11	

WD_12YD

Thermal Limit Curves

Motor Type: AEHHXF		Catalogue No: XH0502C		Family: Optim TEXP	
HP	50	Safe Stall Time		Full Load A	110.0 / 55.0 A
Voltage	230 / 460V 60Hz	Hot	12 s	Locked Rotor A	659 / 660 %
RPM	3600	Cold	17 s	Locked Rotor A	725.0 / 363 A



T-N and I-N Curves

Motor Type: AEHHXF		Catalogue No: XH0502C		Family: Optim TEXP	
HP	50	Full Load T	74 lb-ft	Full Load A	110.0 / 55.0 A
Voltage	230 / 460V 60Hz	Locked Rotor T	185 %	Locked Rotor A	725.0 / 363.0 A
RPM	3600	Pull Up T	115 %	Break Down T	240 %

