

Technical Documentation

APH7/565D

Advantage Plus IEEE Ready | AEHH8R

Date: August 10, 2020

	
	Date: August 10, 2020

Technical Data Sheet

Motor Type: AEHH8R	Catalogue No: APH7/565D
--------------------	-------------------------

Nameplate Information

HP	Pole	RPM	Frame	Voltage	Hz	Phase
7.5	6	1170	254TD	575	60	3
Enclosure	Ins. Class	Service Factor	Time Rating	NEMA Design	Rated Amb.	Rated Altitude
TEFC	F	1.15	Continuous	B	-40 to 40 °C	<1000 m

Typical Performance

Efficiency (%)				Power Factor (%)		
Full Load		3/4 Load	1/2 Load	Full Load	3/4 Load	1/2 Load
Nom.	Min.					
91.0	89.5	91.0	89.5	80.5	75.0	64.0
Torque				Current (A)		
Full Load (lb-ft)	Locked Rotor (% FLT)	Pull Up (% FLT)	Break Down (% FLT)	No Load	Full Load	Locked Rotor
33.66	240	215	270	3.5	7.7	51
NEMA KVA Code	Inertia (WR ²)			Safe Stall Time (s)		Noise Level Sound Press. dB(A)
	Rotor (lb-ft ²)	NEMA Load (lb-ft ²)	Max. Allowable (lb-ft ²)	Cold	Hot	
H	2.158	104.00	375.00	36	25	59

VFD Duty Information

Speed Range			VFD		S.F.
Constant Torque	Variable Torque	Constant Power	Carrier	Type	
6-60Hz	3-60Hz	60-120Hz	≤ 5 kHz	VPWM or CPWM	1.0 Only

Hazardous Locations Information

Additional Certifications

CSA Certified		Other Certification
Class I, Div 2, Groups B, C & D Class I, Zone 2, Groups IIB+H2, IIB & IIA		Class II, Div 2, Groups F & G
Temp Code (Sinewave / VFD)	T3C / T3B	

Additional Information


Bearings		Approx. Weight
DE	NDE	lbs
6309ZC3	6307ZC3	297

Nameplate Drawing

Advantage Plus IEEE Ready

TYPE	AEHH8R		CAT. NO.	APH7/565D		
OUTPUT	7.5 HP 5.6 kW		FRAME	254TD	TEFC	
R.P.M.	1170		POLE	6	INS.	F
VOLTS	575		PHASE	3	Hz	60
AMPS	7.7		CODE	H	S.F.	1.15
AMBIENT	40 °C		NOM. EFF. 91.0		MIN. EFF. 89.5	
BEARINGS	6309ZC3 / 6307ZC3				RATING Cont.	
SER. NO.	TBD		DESIGN	B	WT. 297 LBS	
PWM VFD DUTY	VT	CT	CP		S.F.	
	3-60Hz	6-60Hz	60-120Hz		1.0 Only	

Connection Diagram




3 LEAD		SINGLE VOLTAGE			DELTA
VOLTAGE	CONN.	L1	L2	L3	
-	DELTA	1	2	3	

WD_3D

Thermal Limit Curves

Motor Type: AEHH8R		Catalogue No: APH7/565D		Family: Advantage Plus IEEE Ready	
HP	7.5	Safe Stall Time		Full Load A	7.7 A
Voltage	575V 60Hz	Hot	25 s	% Inrush	665 %
RPM	1200	Cold	36 s	Locked Rotor A	51 A



T-N and I-N Curves

Motor Type: AEHH8R		Catalogue No: APH7/565D		Family: Advantage Plus IEEE Ready	
HP	7.5	Full Load T	33.66 lb-ft	Full Load A	7.7 A
Voltage	575V 60Hz	Locked Rotor T	240 %	Locked Rotor A	51.0 A
RPM	1200	Pull Up T	215 %	Break Down T	270 %

